Specification Sheet



Emergency Safety Shower with Foot and Hand Operated and Eye Face Wash

Product Code: 18-1003

Product Features

When a spill or other accidental contact with dangerous goods threatens the health and welfare of someone on site, a fast, easy to operate response is needed.

This free-standing, Australian made, product delivers; helping safely and effectively flush contaminants and irritants from the eyes and face. Designed for anywhere dangerous goods are used, stored, or transited through, it should ideally be located within 10 seconds' walk of a potential hazard. Immersion of 15 minutes at least is advised.

Replacement valve: 18-1014.

Assembly required.

Faatures

- Eye wash features Vertech™ Technology where dedicated eyewash and independently angled face wash streams deliver optimum coverage
- Zero velocity apex point provides more comfort and control for effective eye cleansing
- Push and foot activated eye/face wash with integral auto-open dust covers
- Easy to operate
- Free-standing
- Self-draining design reduces Legionella risk, particularly in tepid water applications
- Complies with the requirements of ANSI Z358.1 and AS4775

Specifications

- 316 Stainless steel pipe work
- 316 Stainless steel 200mm (8") shower head assembly
- High visibility yellow powder coated push handle and foot pedal
- When activated, water will continuously flow through
- Weight: 12.7kgs
- Dimensions: 2,320mm (height from base to top of shower)

Technical Information

| Inlet connection: | 25 mm (1") BSP |
|-----------------------------------|---|
| Water supply line size: | Must be hydraulically sized to meet requirements |
| Minimum performance requirements: | 210 kPa. Caution should be taken when pressure exceeds 550 kPa (80 psi) |
| Minimum flow requirements: | Shower: 76 lpm (20 US gpm) / Eyewash: 17 lpm (4.5 US gpm) |
| Waste water outlet size: | 38 mm (1 ½") OD |
| Mounting base plate size: | 150 x 150 mm (5 9/10" x 5 9/10") with 4 Bolt Holes 11 mm (7/16") |



