

# Specification Sheet

## Drum Plug - 1kg

Product Code: 22-1003

### Product Features

This compound cuts off potentially devastating spills at the source. Highly recommended as a specialist addition to spill kits, it is a fast, effective way to temporarily seal leaks of hydrocarbons and other hazardous liquids, preventing events escalating. Sticking to even dirty, greasy and rusty surfaces it remains flexible for up to 24 hours after application. Suitable for a wide range of solvents, alcohols, and bases.

Also available in a 250g tub.

NOTE: Not suitable for Phosphoric acid, Hydrofluoric acid, Triethylamine 99%, Sulphuric acid 96% and Hydrogen peroxide 15%.



### Suitable for sealing leaks of the following liquids:

#### Acids:

- Lactic acid
- Hydrochloric acid 37.91%
- Acetic acid 99.50%
- Nitric acid 69.50%

#### Alcohols:

- Ethano
- Propanol
- Methanol 99%
- Mineral Alcohols

#### Bases:

- Sodium hydroxide 40%
- Liquid caustic soda

#### Solvents:

- Trichlorethylen
- Perchlorethylen
- Toluene
- Gasoline
- Hexane

#### Other liquids:

- Ethylenglykolmonobutylether
- Diethylenglykolmonobutylether
- Ethylendichloride 99%
- Amylacetate 99%
- Methylenchloride 99%
- Water based paints
- EDC (acidic)
- EDC (alkaline)
- Methylisobutylketone 99%

### Not suitable for containing the following liquids:

- Phosphoric acid
- Hydrofloric acid
- Triethylamine 99%
- Sulphuric acid 96%
- Hydrogen peroxide