

Drain Protector - Polyurethane

Product Code: 22-1000 | 22-1001

- STEP 1**
- Make sure the Drain Protector is the correct size for the drain(s) on your worksite.
 - For best results, use a Drain Protector that is at least 15cm larger than the outside of the drain.

- STEP 2**
- Be sure all stones, branches, or other debris are removed from the drain you are covering.
 - Remove the plastic film from the Drain Protector and save it to reuse after the incident.
 - Center the Drain Protector over the drain, grate, or manhole you are sealing.
 - There is no need to step on, or place weights on the Drain Protector. The polyurethane material will seal quickly on it's own.



- STEP 3**
- Always wash the Drain Protector for effective reuse and storage.
 - Wash the Drain Protector in warm water with a non-abrasive detergent or petroleum solvent cleaner. Dry with a cloth and re-apply the plastic film.
 - Using the tube provided, roll the Drain Protector and place it back into the box provided for storage **IMPORTANT: Do not store without protective plastic film.**
 - Store the Drain Protector out of direct sunlight, or in a dedicated **Drain Protector Storage Case.**



Compatible chemicals:

- | | | |
|--------------------|--------------------|--------------------------|
| • Aluminum Salts | • Glycol Ether | • Sodium Hydroxide (50%) |
| • Barium Salts | • Hexane | • Tetrachloroethylene |
| • Boric Acid | • Jet Fuel (JP-5) | • Triethylamine |
| • Butanol | • Kerosene | • Turpentine |
| • Calcium Chloride | • Methanol | • Water |
| • Cupric Chloride | • Mineral Oil | |
| • Formaldehyde | • Naptha | |
| • Gasoline | • Propylene Glycol | |